

WENZHOU YUZHENG VALVE

管件系列 Pipe Fitting Series

100

不锈钢丝扣管件系列 Stainless Steel Thread Fittings

特点 Feature:

连接形式: 螺接、软管、堵头 材质为: SUS304, SUS316 管道连接控制: DN8-100及1/4"-4" 适用于各种条件及连接要求
Type:Screwed, hose, plug Material: SUS304, SUS316 Size: DN8-100&1/4"-4" Applicable to various conditions and connection

六角外丝 Hexagon Nipple

SIZE	DN	L	D
1/4	8	22	22
3/8	10	23	25
1/2	15	27	28
3/4	20	30	34
1	25	35	41
1-1/4	32	40	50
1-1/2	40	48	58
2	50	53	69
2-1/2	65	62	89
3	80	69	107
4	100	83	128

管帽 Socket

SIZE	DN	L	D
1/4	8	22	22
3/8	10	23	25
1/2	15	27	28
3/4	20	30	34
1	25	35	41
1-1/4	32	40	50
1-1/2	40	48	58
2	50	53	69
2-1/2	65	62	89
3	80	69	107
4	100	83	128

45° 弯头 45° Elbow

SIZE	DN	SA	L	D
1/4	8	21.0	18.0	18.0
3/8	10	21.5	20.0	20.0
1/2	15	21.5	22.0	22.0
3/4	20	21.5	24.0	24.0
1	25	21.5	26.0	26.0
1-1/4	32	21.5	28.0	28.0
1-1/2	40	21.5	30.0	30.0
2	50	21.5	32.0	32.0
2-1/2	65	21.5	34.0	34.0
3	80	21.5	36.0	36.0
4	100	21.5	38.0	38.0

90° 弯头 90° Elbow

SIZE	DN	L	D
1/4	8	22	22
3/8	10	23	25
1/2	15	27	28
3/4	20	30	34
1	25	35	41
1-1/4	32	40	50
1-1/2	40	48	58
2	50	53	69
2-1/2	65	62	89
3	80	69	107
4	100	83	128

异径弯头 Reducer Elbow

SIZE	DN	L1	D	D1
1/2	15	52	47	34
3/4	20	52	47	34
1	25	52	47	34
1-1/4	32	64	49	51
1-1/2	40	70	57	42
2	50	84	69	51
2-1/2	65	90	70	57
3	80	90	70	57
4	100	90	70	57

Tel: 86-0577-86961077 Fax: 86-0577-86961078 www.valve-yz.com

不锈钢丝扣管件系列 Stainless Steel Thread Fittings

特点 Feature:

连接形式: 螺接、软管、堵头 材质为: SUS304, SUS316 管道连接控制: DN8-100及1/4"-4" 适用于各种条件及连接要求
Type:Screwed, hose, plug Material: SUS304, SUS316 Size: DN8-100&1/4"-4" Applicable to various conditions and connection

三通 Tee

SIZE	DN	L	D
1/4	8	22	22
3/8	10	23	25
1/2	15	27	28
3/4	20	30	34
1	25	35	41
1-1/4	32	40	50
1-1/2	40	48	58
2	50	53	69
2-1/2	65	62	89
3	80	69	107
4	100	83	128

四通 Cross

SIZE	DN	L	D
1/2	15	50	30
3/4	20	56	35
1	25	66	42
1-1/4	32	80	52
1-1/2	40	87	58
2	50	102	70

四角塞头 Square plug

SIZE	A	B	C	D	SW
1/8	13	6.5	15.5	4.5	6
1/4	17.5	11	19	8.7	10
3/8	17.5	11	19	8.7	10
1/2	21	13	19	10.7	12
3/4	24	14.5	21	12.2	17
1	27	16	23	14.5	19
1-1/4	34	23	31	20.5	23
1-1/2	39	27	37	21	26
2	39.5	26.5	38	23.5	31.5
2-1/2	44	31	43	28	36
3	44	30	40	26	36

内外弯头 M/F Elbow

SIZE	DN	L	L1	D
1/2	15	53	35	30
3/4	20	60	42	35
1	25	59	50	42

圆帽盖 Cap

SIZE	DN	A	B	D	
1/8	12.5	13.9	15	5.5	12.6
1/4	14.9	16.9	18	6	12.6
3/8	18.4	20.2	16	6	13.6
1/2	24.9	25.9	20	6	17.5
3/4	29.4	31.4	22	6	19.5
1	37.9	39.9	26	6	23.5
1-1/4	44.9	48.9	30	6	27.5
1-1/2	52.9	55.9	30	6	29.5
2	64.9	67.9	34	6	33.5
2-1/2	83.9	84.9	38	6	39.5
3	94.9	98.4	42	6	39

Tel: 86-0577-86961077 Fax: 86-0577-86961078 www.valve-yz.com

六角管帽 HEX-Cap

特点 Feature:

连接形式: 螺接、软管、堵头 材质为: SUS304, SUS316 管道连接控制: DN8-100及1/4"-4" 适用于各种条件及连接要求
Type:Screwed, hose, plug Material: SUS304, SUS316 Size: DN8-100&1/4"-4" Applicable to various conditions and connection

SIZE	A	C	SW	厚度
1/8	15	15	12.5	6
3/4	14	15	15.8	6
1/2	15	15	15.8	6
1	20	11.5	26.5	6
1-1/4	25	14	31.5	6
1	26	15	38.5	8
1-1/4	28	17	47.5	8
1-1/2	32	17	54	8
2	34	25	66	8
4	44		121.5	8

活帽头 Union

SIZE	DN	L	L1	S	R1
1/4	8	28	15	33	18
3/8	10	39	18	36	22
1/2	15	43	17	39	24
3/4	20	45	19	46	32
1	25	48	21	48	34
1-1/4	32	55	22	56	48
1-1/2	40	60	24	62	54
2	50	64	25	68	66
2-1/2	65	68	27	104	103
3	80	70	28	120	103
4	100	78	30	148	125

内外螺纹活帽头 Union(M/F)

SIZE	DN	L	SW
1/4	8	50	30
3/8	10	57	35
1/2	15	67	42
3/4	20	77	47
1	25	88.3	53
1-1/4	32	104	61
1-1/2	40	113.3	72
2	50	137	84
4	100	154.3	137

异径管帽 Reducing Socket

SIZE	DN	D	D1
1/2	15	33	25
3/4	20	33	25
1	25	33	25
1-1/4	32	44	34
1-1/2	40	44	34
2	50	53	42
2-1/2	65	53	42
3	80	53	42
4	100	53	42

补芯 Bushing

SIZE	DN	L	H
1/4	8	15	19
3/8	10	20	20
1/2	15	25	24
3/4	20	30	25
1	25	35	26
1-1/4	32	45	30
1-1/2	40	50	33
2	50	60	37
2-1/2	65	65	41
3	80	80	48
4	100	118	51

Tel: 86-0577-86961077 Fax: 86-0577-86961078 www.valve-yz.com

不锈钢丝扣管件系列 Stainless Steel Thread Fittings

特点 Feature:

连接形式: 螺接、软管、堵头 材质为: SUS304, SUS316 管道连接控制: DN8-100及1/4"-4" 适用于各种条件及连接要求
Type:Screwed, hose, plug Material: SUS304, SUS316 Size: DN8-100&1/4"-4" Applicable to various conditions and connection

抛光管子接头丝 Half-nipple

SIZE	A	B	C
1/2	18	21.3	25
3/4	20	26.9	30
1	25	32.7	40
1-1/4	30	42.4	40
1-1/2	20	48.3	40
2	22	60.3	43
2-1/2	22	76.1	45
3	25	88.9	45

抛光管子双头丝 Barrel-nipple

SIZE	S	L	A
1/4	2.0	40	10
3/8	2.0	60	10
1/2	2.5	80	10
3/4	2.5	60	10
1	3.2	60	18
1-1/4	3.2	80	21
1-1/2	3.2	100	24
2	3.6	100	24
2-1/2	4.0	120	24
3	4.0	120	24
4	4.5	120	24

抛光管子内丝 Coupling

SIZE	D1	D2	L
1/4	18	18	18
3/8	25	25	25
1/2	28	28	30
3/4	34	34	30
1	40	40	35
1-1/4	40	40	40
1-1/2	55	55	40
2	65	65	50
2-1/2	80	80	50
3	100	100	50
4	127	127	50

抛光管子外丝 Hose Nipple

SIZE	DN	L	D
1/2	15	90	30
3/4	20	96	35
1	25	66	42
1-1/4	32	80	52
1-1/2	40	87	58
2	50	102	70

水管接头 Hexagon Hose Nipple

SIZE	DN	OD	L	SW
1/4	8	6.35	47.0	16.5
3/8	10	9.50	56.0	20.0
1/2	15	12.70	64.0	23.5
3/4	20	19.05	68.0	31.0
1	25	25.40	71.0	38.5
1-1/4	32	31.80	80.0	46.0
1-1/2	40	38.10	95.0	56.0
2	50	50.80	105.0	62.0
2-1/2	65	63.50	107.0	69.0
3	80	76.20	112.0	91.0
4	100	101.60	130.0	118.5

Tel: 86-0577-86961077 Fax: 86-0577-86961078 www.valve-yz.com

高压管件系列 High-Pressure Fittings Series

特点 Feature:

连接形式: 螺接、软管、堵头 材质为: SUS304, SUS316 管道连接控制: DN8-100及1/4"-4" 适用于各种条件及连接要求
Type:Screwed, hose, plug Material: SUS304, SUS316 Size: DN8-100&1/4"-4" Applicable to various conditions and connection

内螺纹三通 Tee

高压90°弯头 Elbow

高压45°弯头 45° Elbow

接口接头直通 Union

高压堵头 Plug

高压六角外丝 Hex nipple

高压管子内丝 Coupling

锻钢螺纹四通 Forged steel Thread Cross

RATING:
PRESSURE: THREADED END-2000/3000/6000 LBS.
SOCKET-WELD END-3000/6000/9000 LBS.
BUTT WELDEND-SCH40/SCH80/SCH160/XXS.

SPECIFICATIONS:
A. DIM. SPEC.:
CB/T 7306, 12716, 14383, 14626
ASME B16.11-2001 (REVISION OF ASME 16.11-1996)
MSS-SP-79, 83, 95, 97
B. MATERIAL SPEC:
ASTM A105, A350 LF, A106, A312, A234, A403
GB/T 699 20MM
ASTM A182(F304, F304L, F316, F316L, F304H, F316H, F317L, F321, F11, F22, F61, F51, F55, 904L, F44).
GB(0Cr18Ni10Ti, 0Cr18Ni9, 0Cr19Ni10, 0Cr17Ni2Mo2, 0Cr17Ni14Mo2, 0Cr19Ni15Mo3.5, 0Cr18Ni11Nb, 0Cr25Ni20).

SIZE OF RAW MATERIAL: DIA. 19-100MM ROUND BAR.

Tel: 86-0577-86961077 Fax: 86-0577-86961078 www.valve-yz.com

承插焊接配件 Socket-Welding Fittings

ASME B16.11-2005/ASME B16.11-2001(修订图)

90° 弯头 90° ELBOW 四通 CROSS 三通 TEE 45° 弯头 45° ELBOW

尺寸单位为毫米 Dimensions in Millimeters.

公称管子规格 Nom. Pipe Size DN	Socket Bore Dia.(D2)	管子外径 Bore Diameter of Fitting D			承插口深度 Socket Wall Thickness(1) C			本体厚度 Body Wall Thickness G			接口深度 Depth of Socket J						
		3000	6000	9000	3000	6000	9000	3000	6000	9000							
6	1/8	11.2	7.6	4.8	3.18	3.18	3.96	3.46	2.41	3.15	9.5						
8	1/4	14.6	10.0	7.1	3.78	3.30	4.60	4.01	3.02	3.68	9.5						
10	3/8	18.0	13.3	9.9	3.90	4.27	6.96	6.04	9.78	8.56	3.91	5.66	7.82	12.5			
15	1/2	22.0	16.6	12.5	4.27	4.67	4.09	5.97	5.18	9.35	8.18	3.73	4.78	7.47	9.5		
20	3/4	27.6	21.7	16.8	11.8	10.3	3.90	4.27	6.96	6.04	9.78	8.56	3.91	5.66	7.82	12.5	
25	1	34.3	27.4	21.5	33.9	25.9	19.9	5.69	4.98	7.92	6.93	11.38	9.96	4.55	6.35	9.09	12.5
32	1-1/4	43.1	35.8	30.2	23.5	22.0	6.07	5.28	5.98	6.93	12.14	10.62	4.85	6.35	9.70	12.5	
40	1-1/2	49.2	41.6	34.7	28.7	27.2	6.35	5.54	8.92	7.80	12.70	11.12	5.08	7.14	10.15	12.5	
50	2	61.7	53.3	43.6	38.9	37.4	6.93	6.04	10.92	9.50	13.84	12.12	5.54	8.14	11.07	16.0	
65	2-1/2	74.4	64.2	51.2	47.4	46.2	8.76	6.77		7.01			7.01			16.0	
80	3	90.3	79.4	69.8	61.2	60.2	9.52	8.30		7.62			7.62			16.0	
100	4	115.2	103.8	91.2	81.2	80.2	10.69	9.35								19.0	

NOTES:
(1) Average of Socket Wall Thickness around periphery shall be no less than listed values.
(2) The minimum values are permitted in localized areas.
(3) Upper and lower values for each size are the respective maximum and minimum diameter.

注: